

A AUTOCLAVES Table Top



STE-TEN

STE-TEN, 1 Liter Autoclave

It adopts B-class (prED-13060), with 3-times pre-vacuum preceding vacuum drying. Residual humidity is $\lt; 0.2$, vacuum measurement reaches -0.7bar .

It sterilizes and sanitizes miscellaneous packed or unpacked medical instruments, whether solid or A-type hollow, whether with multi-apertures or inset pipes. It efficiently rid air from every hollow area of any hollow instrument, such as hand-piece, making sure that water steam reaches every corner. It is installed with BOWIC & DICK which measures the penetration of water steam. Mini printer can be attached to record the process of sterilization.



Model	Voltage (V/Hz)	Power (W)	Capacity (L)	Chamber size	Outside size(mm)	Weight (kg)
STE-TEN	220/50	1100	1	Ø90x160mm	W200xH385xD450	30 (Net:28)



STE-TAN-8L

STE-TAN-8L, 8 Liter Autoclave

Adopting European N standard, with thermal vacuuming & drying function, it can be used for A type hollow instruments and solid instruments

Technical feature:

- Sterilization temperature: 121, 134 Cent degrees
- Drying Program: Thermal Vacuum drying
- Digital display
- Sterilization record: mini external printer is available
- Safety: safety valve, temperature control, pressure protection system, temperature protector of chamber wall
- Sterilization and drying time adjustable help you to get the best sterilization effect
- Open type water storage tank
- Quick drain connector
- Optional type B: STE-8L(B).

Model	Voltage (V/Hz)	Power (W)	Capacity (L)	Chamber Size (mm)	Outside size (mm)	Weight (kg)
STE-8LN	AC220V/50Hz	1400W	8L	Φ170x320mm	W345xH530xD340	34 (Net:30)
STE-8LB		1500W				37 (Net:34.5)



STE-TAN

STE-TAN, 16 Liter Autoclave

Adopting N-class (prED-13060), with thermal vacuumizing and drying function, it can be used for A-type hollow instruments & solid instruments. Thermodynamic vacuum guarantees elimination of cold air from the cavity and makes sure of perfect saturation of water dream. Three sterilizing water quantity selections are respectively for different material, which embodies the individualized service Automatic malfunction detecting system makes easy maintaining.

- Liquid Sterilizing option
- Optional Printer



Model	Voltage (V/Hz)	Power (W)	Capacity (L)	Chamber size	Outside size (mm)	Weight (kg)
STE-TAN	220/50	1900	16	Ø230x360mm	W440xH400xD560	64 (Net:43)